



TECHNICAL DATA SHEET



InJet® 388 CRRD

- ★★★ PCB cleaning
- ★★★ STENCIL cleaning
- ★★★ PUMPRINT cleaning





TECHNICAL PARAMETERS

Dimensions (w x l x h)	1050 x 1325 x 1850 mm
External rinsing set dimensions (w x l x h)	1000 x 800 x 1100 mm
Weight	350 kg
External rinsing set weight	210 kg
Ø energy consumption per 1 cycle	1,65 kWh
Cleaning fluid consumption per 1 cycle	0,05 – 0,3 l
Compressed air consumption per 1 cycle	3 l / 5 Bar
Max. dimensions of the cleaned parts	190 x 860 x 790 mm
Exchangeable mechanical filter of cleaning fluid	20 - 100 µm
Exchangeable mechanical filter of rinsing fluid	5 - 20 µm
Operating pressures	cleaning 1,5 Bar - 2,8 Bar 1. rinsing 0,1 Bar - 0,8 Bar 2. rinsing 0,3 Bar - 1,5 Bar
Cleaning fluid flow rate	125 l/min
Temperature range setting of the cleaning fluid	From ambient temperature to 60°C
Temperature range setting of the 1. rinse fluid	From ambient temperature to 60°C
Temperature range setting of the 2. rinse fluid	From ambient temperature to 60°C
Conductivity range settings of the rinse fluid	0 – 200 µS/cm
Temperature range setting of the drying	From ambient temperature to 80°C
Noise level	< 70 dB
Device control	PLC + 8,4" touchscreen



INSTALLATION REQUIREMENTS

Power supply	400 V, 50Hz (3+N+PE)
Power connection	EU 32 A
Pmax	12 kW
Connection to central air pressure	Pipe Ø 6 mm
Recommended working pressure	5 Bar
Exhaust pipe diameter	Ø 100 mm
Exhaust pipe capacity	380 m³/h
Volume of the storage tanks for cleaning	50 l
Volume of the storage tanks for 1. and 2. rinsing	60 a 50 l
Service space required around the device	600 mm



4 INDIVIDUAL PROCESSES



CLEANING




2. RINSING



1. RINSING



DRYING



CLEANING PARAMETERS

Application name	Application recommended	Recommended temperature	Recommended time	Capacity per shift
PCB	★★★	35 – 55°C	30 min.	384*
Stencils	★★★	20 – 40°C	18 min.	27
Pumprints	★★★	40 – 55°C	38 min.	13

★★★ highly recommended

* eurocards (100x160 mm) per 8 hours (work shift)



PARTS OF THE STANDARD DELIVERY

touch panel with 2 level access: operator, technician

active regeneration for 1. rinsing circuit

100% closed circuit

exhaust valve

status light

draft diverter

lockable travelling wheels



CONTINUOUS MONITORING

cleaning and 2. rinsing fluid temperature

drying temperature

fluid pressure

fluid min. and max. level

1. and 2. rinse conductivity

number of cleaning, rinsing, drying cycles for fluid and filter exchanges



MAIN OPTIONAL ACCESORIES

bar code reader + SW

fluid leakage tray

speed control of rotation arms

active regeneration for 2. rinsing circuit

online, offline traceability

three arms rotation

air knife for increase of efficiency of drying and reduction of contamination of rinse liquid
+ other accessories according the Map of accesories



Date of issue: **1 April, 2015**

InJet® is a registration trademark of DCT Czech s.r.o.

For next information about InJet® 388 CRRD can you contact DCT specialist in Your country or to manufacturer directly.

DCT Czech s.r.o., Tovární 85, 679 21 Černá Hora, Czech republic
e-mail: info@dct.cleaning